CERTIFICATE OF CONFORMITY CERTIFICATO DI CONFORMITÀ

Issued to: Renac Power Technology Co., Ltd.

Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech

District, Suzhou, China

For the product: PV Grid-tied Inverter

Trade name:

Type/Model: R1-3.68K1, R1-4K1, R1-5K1, R1-6K1

Ratings: See Annex

Manufactured by: Renac Power Technology Co., Ltd.

Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech

District, Suzhou, China

Requirements: IEC 61683:1999

This Test Certificate is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6200378.50

The examination has been carried out on one single specimen of the product. The certificate does not include an assessment of the minilecture's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This Test Certificate expires at the latest on 2029-09-27 or expires upon withdrawal of one of the above mentioned standards.

Shanghai, 27 September 2024 Number: 6200378.01COC

DEKRA Testing and Certification (Shanghai) Ltd.

Clidan

Cliff Lin Certification Manager

© Integral publication of this certificate and adjoining reports is allowed

ACCREDITED
Product Certification
Agency
PCA-141

DEKRA Testing and Certification (Shanghai) Ltd.

No.250, Jiangchangsan Road, Jing'an District, Shanghai, 200436 People's Republic of China
T+86 21 6056 7600 F+86 21 6056 7555 www.dekra-product-safety.com
ESA-CER-F021 v4.1

Annex



Document no. : 6200378.01COC

Ratings of product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP65

OVC: DC II / AC III

Power factor range (adjustable): (0.8 leading...0.8 lagging)

R1-3.68K1

PV Input: Max 600 Vdc, MPPT voltage range: 80-550 Vdc, Max 20 A, Isc PV: 25 A

AC Output: 220 / 230 Vac, L/N/PE, 50 / 60 Hz, Max current:16 A, Max 3680 VA, rated active power: 3680 W

R1-4K1

PV Input: Max 600 Vdc, MPPT voltage range: 80-550 Vdc, Max 20 A, Isc PV: 25 A

AC Output: 220 / 230 Vac, L/N/PE, 50 / 60 Hz, Max current: 20 A, Max 4400 VA, rated active power: 4000 W

R1-5K1

PV Input: Max 600 Vdc, MPPT voltage range: 80-550 Vdc, Max 20 A, Isc PV: 25 A

AC Output: 220 / 230 Vac, L/N/PE, 50 / 60 Hz, Max current:25 A, Max 5500 VA, rated active power: 5000 W

R1-6K1

PV Input: Max 600 Vdc, MPPT voltage range: 80-550 Vdc, Max 20 A, Isc PV: 25 A

AC Output: 220 / 230 Vac, L/N/PE, 50 / 60 Hz, Max current:27.3 A, Max 6000 VA, rated active power: 6000 W

--END--