

Residential On-grid Inverter


# R1 Macro Series

3.68kW / 4kW / 5kW / 6kW



## Features

Single Phase, 2 MPPTs

-  Compatible with 500W+ PV modules
-  Optional AFCI protection function
-  150% PV input oversizing
-  Remote firmware upgrade
-  Type II SPD for both DC and AC
-  Built-in zero export function



Model	R1-3.68K	R1-4K	R1-5K-A	R1-5K	R1-6K
<b>PV Input</b>					
Max. Recommended PV Power [Wp]	5500	6000	7500	7500	9000
Max. PV Power for single MPPT [Wp]	2800	3000	3750	3750	4500
Max. PV Input Voltage [V]	600				
MPPT Voltage Range [V]	80 ~ 550				
Rated PV Input Voltage [V]	360				
Start-up Voltage [V]	100				
No. of MPP Trackers	2				
No. of Input Strings per Tracker	1 / 1				
Max. PV Input Current [A]	16 / 16				
Max. Short-circuit Current [A]	20 / 20				
<b>AC Output</b>					
Rated AC Output Power [W]	3680	4000	5000	5000	6000
Max. AC Output Apparent Power [VA]	3680	4400	5000	5500	6000
Max. AC Output Current [A]	16	20	21.7	25	27.3
Rated AC Voltage [V]	L / N / PE, 220 / 230				
Grid Frequency [Hz]	50 / 60				
Adjustable Power Factor [cosφ]	0.8 leading ~ 0.8 lagging				
Output THDi (@Rated Output)	< 3%				
<b>Efficiency</b>					
Max. Efficiency	97.9%	97.9%	97.9%	97.9%	97.9%
Euro Efficiency	97.2%	97.2%	97.2%	97.2%	97.2%
<b>Protection</b>					
DC Insulation Monitoring	Integrated				
Input Reverse Polarity Protection	Integrated				
Anti-island Protection	Integrated				
Residual Current Monitoring	Integrated				
AC Overcurrent Protection	Integrated				
AC Short-circuit Protection	Integrated				
DC Surge Protection	Integrated (Type II)				
AC Surge Protection	Integrated (Type II)				
AFCI Protection	Optional				
DC Switch	Optional				
<b>General Data</b>					
Dimensions (W * H * D) [mm]	353 * 320 * 150				
Weight [kg]	10				
Display	LED + OLED				
Communication	RS485, USB Update, Optional: WiFi, 4G, Ethernet				
Ambient Temperature Range [°C]	-25 ~ +60				
Relative Humidity	0 ~ 100%				
Operating Altitude [m]	≤ 2000				
Night Self-consumption [W]	< 1				
Topology	Transformerless				
Cooling	Natural				
Ingress Protection	IP65				
Noise [dB]	< 25				
<b>Certifications &amp; Standards</b>					
Grid Regulation	VDE 0126-1-1, ORDINANCE No.140, G98/G99				
Safety Regulation	IEC 62109-1, IEC 62109-2, EN 62919-1, EN 62619-2				
EMC	EN IEC 61000-6-1, EN IEC 61000-6-3				