ATTESTATION OF CONFORMITY

Issued to:	Renac Power Technology Co., Ltd. Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech District, Suzhou, China
For the product:	PV Grid-tied Inverter
Trade name:	RENAC
Type/Model:	R1-8K, R1-10K, R1-10K5
Ratings:	See model list
Manufactured by:	Renac Power Technology Co., Ltd. Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech District, Suzhou, China
Requirements:	EN IEC 61000-6-1:2019 EN IEC 61000-6-3:2021

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6183569.50

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic compatibility directive 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 25 April 2024

Number: 6183569.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kreng Lin

Kreny Lin Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2



DEKRA Testing and Certification (Shanghai) Ltd. 3F #250 Jiangchangsan Road Shibei Hi-Tech Park, 200436 Jing'an District, Shanghai, China T +86 21 6056 7666 F +86 21 6056 7555 www.dekra-product-safety.com



Annex

Document no. : 6183569.01AOC

Model list:

Product Model	PV Input	Output
R1-8K	Max. 600 Vdc, MPPT voltage range: 80-550	L/N/PE 220/230 Vac, 50/60 Hz, max 40 A,
	Vdc, max: 32/32 A, Isc PV: 40/40 A	max 8800 VA
R1-10K	Max. 600 Vdc, MPPT voltage range: 80-550	L/N/PE 220/230 Vac, 50/60 Hz, max 45.5 A,
	Vdc, max: 32/32 A, Isc PV: 40/40 A	max 10000 VA
R1-10K5	Max. 600 Vdc, MPPT voltage range: 80-550	L/N/PE 220/230 Vac, 50/60 Hz, max 45.5 A,
	Vdc, max: 32/32 A, Isc PV: 40/40 A	max 10500 VA

End